

90101135 SIMPLE 2

FUNCTIONS



Backrest adjustment : 0 - 70°



Thigh rest adjustment : 0 - 40°



Foot rest mechanical adjustment : 0 - 25°



Vascular position



Fowler position



Mattress platform minimum height : 45 cm
Mattress platform maximum height: 85 cm

HOSPITAL BED 3 MOTORS

OPTIONS

GROUP 1 / CASTOR OPTIONS



GROUP 2 / BOARD OPTIONS



GROUP 3 / SIDE RAIL OPTIONS



GROUP 4 / OTHER ACCESSORY OPTIONS



DESCRIPTION OF OPTION CODES

T0 WITHOUT CASTORS

T16 CASTOR TWO WITH BRAKE (125 MM)

T4 METAL CASTOR WITH BRAKE (125 MM)

B1 METAL BOARD

B2 PE PLASTIC BOARD

K0 WITHOUT SIDE RAIL

K1 WITH METAL SIDE RAIL

K3 WITH METAL SIDE RAIL

W0 WITHOUT OTHER ACCESSORIES

W2 LIFTING POLE : BEARING CAPACITY 75 Kg

W4 TELEVISION STAND FOR 17" LCD TV

W5 TRACTION APPARATUS

W8 IV STAND : ONE HEIGHT ADJUSTMENT SYSTEM

Must select only one of them.

Do not select the others if you select without accessory. If you select the others you can select all or 1-2-3 ... of them.

GENERAL SPECIFICATIONS

- Ergonomic, comfortable, and durable semi-electric home-care bed.
- Plastic laminated head and foot panels.
- 4-section metallic mattress platform and metallic side-rails
- Electrically-adjustable height, backrest section, and legrest section, all controlled by a single handset.
- IV pole sockets at the four corners.
- Four lockable (12.5 cm) diameter swiveling castors with four bumpers.
- Metal components dyed with anti-corrosion electrostatic powder paint after being treated with phosphate.
- German made Okin brand motors
- Optional laminate color choice.^(RLX)

TECHNICAL SPECIFICATIONS

■ External dimension	: 105 x 210 cm
■ Recommended mattress dimension	: 85 x 194 x 12 cm
■ Safe Operating Load (Inc. Mattress and Accessories)	: 230 kg
■ Maximum Static Load	: 400 kg
■ Weight	: ~ 96 kg
■ Volume	: 1,1 m ³
■ Under bed clearance	: 16 cm

ELECTRICAL SPECIFICATIONS

■ Power Input	: 230 V AC 50 / 60 Hz 50W
■ Power Output	: 24 V DC



* RL : Laminate color options page 82.