

90101212.17 SIMPLE 11

FUNCTIONS



Backrest adjustment : 0 - 70°



Thigh rest adjustment : 0 - 40°



Foot rest mechanical adjustment : 0 - 25°



Vascular position



Fowler position



Trendelenburg position : 0 - 12°

HOSPITAL BED WITH 3 CRANKS

OPTIONS


GROUP 1 / CASTOR OPTIONS



GROUP 2 / SIDE RAIL OPTIONS



GROUP 3 / OTHER ACCESSORY OPTIONS



DESCRIPTION OF OPTION CODES

T1 TWIN CASTOR TWO WITH BRAKE (120 MM)	K3 WITH METAL SIDE RAIL
T16 CASTOR TWO WITH BRAKE (125 MM)	W0 WITHOUT OTHER ACCESSORIES
T4 METAL CASTOR TWO WITH BRAKE (125 MM)	W2 LIFTING POLE : BEARING CAPACITY 75 Kg
T14 CASTOR CENTRAL & DIRECTIONAL LOCK (125 MM)	W4 TELEVISION STAND FOR 17" LCD TV
T17 CASTOR CENTRAL & DIRECTIONAL LOCK (150 MM)	W5 TRACTION APPARATUS
K0 WITHOUT SIDE RAIL	W8 IV STAND : ONE HEIGHT ADJUSTMENT SYSTEM
K1 WITH METAL SIDE RAIL	

Must select only one of them.

Do not select the others if you select without accessory. If you select the others you can select all or 1-2-3 ... of them.

GENERAL SPECIFICATIONS

- Type : General purpose
- Design : All parts of the bed Heavy duty & compact design with high finishing.
- Construction : Steel epoxy powder coated
- Section : Four section mattress platform.
- Manual crank functions : Head, back, foot knee, trendelenburg
- Mattress support type : Pan
- Pair of side rails : Easy movable
- Castors : Antistatic four castor with central locking system
- Protection : Four rubber buffer provided to prevent damage to hospital walls
- Head and foot panel : Included
- IV pole mounts : Included
- Lifting Pole : Heavy duty
- Mattress : Original conductive, antibacterial, anti acid antistatic, waterproof for easy use and care.
- Chart holder : Original and heavy duty
- Optional melamine coated chipboard color choice. ^(RSX)

TECHNICAL SPECIFICATIONS

■ Overall dimension	: 100 x 210 x 50 cm
■ Safe Operating Load (Inc. Mattress and Accessories)	: 230 kg
■ Weight	: ~ 85 kg
■ Volume	: 1,13 m ³



* RS : Melamine color options page 83.